

Claims

What is claimed is:

1. A process, comprising the step of:

computing one or more parameters of a fiber optic gyroscope through employment of a closed-loop transfer function based on one or more characteristics of:

one or more optical components of the fiber optic gyroscope; and
one or more electrical components of the fiber optic gyroscope.

2. The process of claim 1, wherein the step of computing the one or more parameters of the fiber optic gyroscope through employment of the closed-loop transfer function based on the one or more characteristics of the one or more optical components of the fiber optic gyroscope and the one or more electrical components of the fiber optic gyroscope comprises the step of:

computing one or more performance parameters of the fiber optic gyroscope through employment of one or more physical parameters of one or more of the one or more optical components and one or more of the one or more electrical components.

3. The process of claim 2, wherein the step of computing the one or more performance parameters of the fiber optic gyroscope through employment of the one or more physical parameters of the one or more of the one or more optical components and the one or more of the one or more electrical components comprises the steps of:

determining one or more relationships between the one or more performance parameters and the one or more physical parameters; and

employing one or more of the one or more relationships to compute the one or more performance parameters.

4. The process of claim 3, wherein the step of employing the one or more of the one or more relationships to compute the one or more performance parameters comprises the steps of:

substituting one or more known values of the one or more physical parameters into the one or more relationships; and

employing the one or more known values of the one or more physical parameters to compute the one or more performance parameters.

5. The process of claim 3, further comprising the step of:

determining one or more desired values of the one or more physical parameters for employment in causation of the one or more performance parameters to equal or approach one or more provided performance parameter values for the fiber optic gyroscope.

6. The process of claim 5, wherein the step of determining the one or more desired values of the one or more physical parameters for employment in causation of the one or more performance parameters to equal or approach the one or more provided performance parameter values for the fiber optic gyroscope comprises the step of:

employing the one or more desired values of the one or more physical parameters to design the fiber optic gyroscope to equal or approach the one or more provided performance parameter values.

7. The process of claim 3, wherein the step of employing the one or more of the one or more relationships to compute the one or more performance parameters comprises the step of:

employing the one or more of the one or more relationships and one or more initial values of the one or more physical parameters to compute the one or more performance parameters.

8. The process of claim 7, wherein the step of employing the one or more of the one or more relationships and the one or more initial values of the one or more physical parameters to compute the one or more performance parameters comprises the steps of:

determining a difference between the one or more performance parameters and one or more provided performance parameter values for the fiber optic gyroscope;

iteratively adjusting one or more of the one or more initial values of one or more of the one or more physical parameters through employment of the one or more of the one or more relationships; and

iteratively computing the one or more performance parameters through employment of the one or more of the one or more relationships and the one or more of the one or more initial values.

9. The process of claim 2, wherein the one or more physical parameters comprise one or more of:

an optical power of a light beam in a representation of a first phase modulator in a representation of a feedforward component of the closed-loop transfer function of the fiber optic gyroscope;

an operating phase bias applied to one or more counterpropagating light beams in the representation of the first phase modulator in the representation of the feedforward component of the closed-loop transfer function of the fiber optic gyroscope;

a photodetector scale factor in a representation of a photodetector in a representation of a signal digitizer in the representation of the feedforward component of the closed-loop transfer function of the fiber optic gyroscope;

a preamplifier impedance in a representation of a preamplifier in the representation of the signal digitizer in the representation of the feedforward component of the closed-loop transfer function of the fiber optic gyroscope;

a preamplifier gain of the preamplifier in the representation of the signal digitizer in the representation of the feedforward component of the closed-loop transfer function of the fiber optic gyroscope;

a gain in voltage in a representation of a filter after the photodetector and the preamplifier and before an analog-to-digital converter in the representation of the signal digitizer in the representation of the feedforward component of the closed-loop transfer function of the fiber optic gyroscope;

a gain in a representation of the analog-to-digital converter of the representation of the signal digitizer in the representation of the feedforward component of the closed-loop transfer function of the fiber optic gyroscope;

a digital truncation gain in a representation of a truncator in a representation of a demodulator in a representation of a feedback component of the fiber optic gyroscope;

a transit time for the light beam to propagate through a representation of an optical waveguide in the representation of the feedback component of the closed-loop transfer function of the fiber optic gyroscope; and

a phase modulator scale factor in a representation of a second phase modulator in the representation of the feedback component of the closed-loop transfer function of the fiber optic gyroscope.

10. The method of claim 1, wherein the closed-loop transfer function comprises one or more of:

a summing point that receives:

an input based on a rate of rotation of an optical waveguide of a feedback component and a scale factor based on a wavelength of light propagating through the optical waveguide, an optical path length of the optical waveguide, and a diameter of the optical waveguide, as a positive input; and

an input based on a modulated first light beam and a modulated second light beam exiting the optical waveguide of the feedback component as a negative input;

wherein the summing point employs the positive input and the negative input to determine a difference between the positive input and the negative input;

a feedforward component that receives the difference between the positive input and the negative input as an input;

wherein the feedforward component employs the difference between the positive input and the negative input to provide a signal proportional to a phase difference between the modulated first light beam and the modulated second light beam exiting the optical waveguide of the feedback component as an output;

wherein the feedback component receives the signal proportional to the phase difference between the modulated first light beam and the modulated second light beam exiting the optical waveguide of the feedback component as an input;

wherein the feedback component employs the signal proportional to the phase difference between the modulated first light beam and the modulated second light beam exiting the optical waveguide of the feedback component to produce a feedback signal;

wherein the feedback component employs the feedback signal to produce the modulate first light beam and the modulated second light beam exiting the optical waveguide of the feedback component.

11. An article, comprising:

one or more storage media readable by a processor;

means in the one or more storage media for computing one or more parameters of a fiber optic gyroscope through employment of a closed-loop transfer function based on one or more characteristics of:

one or more optical components of the fiber optic gyroscope; and

one or more electrical components of the fiber optic gyroscope.

12. The article of claim 11, wherein the means in the one or more storage media for computing the one or more parameters of the fiber optic gyroscope through employment of the closed-loop transfer function based on the one or more characteristics of the one or more optical components of the fiber optic gyroscope and the one or more electrical components of the fiber optic gyroscope comprises:

means in the one or more storage media for determining one or more relationships between one or more physical parameters and one or more performance parameters of:

one or more of the one or more optical components; and

one or more of the one or more electrical components; and

means in the one or more storage media for employing one or more of the one or more relationships to determine the one or more performance parameters.

13. The article of claim 12, wherein the one or more performance parameters comprise one or more of a bandwidth of the fiber optic gyroscope, a coefficient of random walk of the fiber optic gyroscope, an operating frequency of the fiber optic gyroscope, and a power spectral density of noise of the fiber optic gyroscope.

* * * * *